



# Impressions™ *ClimaPlus*™



IMPRESSIONS Panels with *CLIMAPLUS* Superior Performance/  
DONN Centricitee DXT Suspension System

### ESD Information

Recycled Content: 44%  
*CLIMAPLUS* Superior Performance for Mould/Mildew

★ Contributes to Green Star points    ✓ ESD additional advantages

IEQ						Ene	Mat
Increase Daylight Levels	Reduce Lighting Levels	Internal Noise Level Reduction	Low Volatile Organic Compounds	Low Formaldehyde	Mould Prevention	Lighting Density Reduction	Design for Disassembly
★	★	★	✓	✓	✓	★	✓

### Advantages

- Micro fissure non-directional pattern for a cleaner, whiter appearance.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 40°C/95% relative humidity without visible sag when used with a DONN® brand suspension system.

### Applications

- Schools
- Corridors
- Lobby areas
- Offices
- Retail stores
- Cinemas / Theatres
- Restaurants / Cafes

### Substrate

- Water-felted mineral fibre



Medium-textured panel

### Grid Options

DONN DX 24mm



DONN Centricitee 15mm



**30**  
 Year System Warranty  
 - No visible sag  
 - Mould/mildew protection

**IMPRESSIONS**  
**CLIMAPlus Panels**

Edge	Panel Size <sup>1,2</sup>	Class	Item No	NRC <sup>3</sup>	CAC <sup>3</sup>	LR <sup>4</sup>	Colour	Grid Options	VOC Emissions	Anti-Mould & Mildew <sup>5</sup>	Recycled Content
 SQ  SLT  FLB	600 x 600 x 15mm	Class A	ME903	.50-.60	33-35	.84	White	A	Low		44%
	1200 x 600 x 15mm	Class A	ME904	.50-.60	33-35	.84	White	A	Low		44%
	600 x 600 x 15mm	Class A	ME905	.50-.60	33-35	.84	White	B	Low		44%
	1200 x 600 x 15mm	Class A	ME908	.50-.60	33-35	.84	White	B	Low		44%
	600 x 600 x 15mm	Class A	ME916	.50-.60	33-35	.84	White	C	Low		44%

**Legend**

**Low Emissions (VOC Class)**

Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods. Low-emitting is defined as having less than 13.5 ppb.

**CLIMAPlus Superior Performance**

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mould/mildew.

Grid Profile Options	A	B	C
	DX®	DX	Centricitee DXT

**Physical Data/ Footnotes**

**Weight**  
 3.0 kg/m<sup>2</sup>

**Environmental Limitations**  
 40°C, 95% RH max.

**Thermal Resistance**  
 R 0.25 m<sup>2</sup>°C/W

**Maximum Backloading**  
 0 kg/m<sup>2</sup>

**Early Fire Performance**

Index	Ignitability	Spread of Flame	Heat Evolved	Smoke Developed
AS/NZS 1530.3	0	0	0	2
ASTM E84	-	25	-	50
AS/NZS 3837	Group 1 – unsprinklered			

**Maintenance**

Can be cleaned easily with a soft brush or vacuum

**Footnotes**

- Not all panel sizes available in all geographic areas
- Some imperial sizes available to order
- Acoustic Test Standards  
 NRC to ASTM C423  
 CAC to ASTM E1414
- LR values are shown as averages
- Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mould/mildew.
- Trademarks used herein belong to USG Interiors, Inc or a related company

**Safety First!**

Follow good safety and industrial hygiene practices during handling and installing of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.



green building council australia  
 MEMBER